

SR-Motard 50 Product Guide



SR-Motard 50

ENGINE

- 50cc displacement
- 4 stroke
- 4 valve





Aluminum Wheels • Front - 120/70 - 14"

• Rear - 120/70 - 14"

aprilia

SR-Motard 50 - Highlights



Two-Tone Saddle

 \triangleright



 Class leading suspensions

SR-Motard 50 vs. Competitors



	Sr-Motard 50		Yamaha Zuma 50F		Honda Ruckus		Honda Metropolitan		Kymco Agility 50		Genuine Buddy 50	
Engine	50cc, single- cylinder, four- stroke 4 valves	۳	single-cylinder 4 strokes	•	single-cylinder 4 strokes	•	single-cylinder 4 strokes	•	single-cylinder 4 strokes	•	50cc 2-Stroke	۳
Cooling	Air	•	Liquid	-	Liquid	•	Air	-	Air	•	Air	•
Fuel supply	Carburetor		Injection	<u> </u>	Carburetor		Injection	•	Carburetor	-	n.a.	
Maximum power	3.4 kW at 9,500 rpm	-	n.a.		n.a.	-	n.a.		n.a.		n.a.	
Starter	Electric and kick starter	•	Electric	-	Electric	-	Electric	-	Electric and kick starter	•	n.a.	
Timing system	4 valve single overhead camshaft		3v SOHC		2 v SOHC		n.a.		2v SOHC		n.a.	
Fuel Economy	144 mpg	•	132 mpg	•	114 mpg		117 mpg	:	87 mpg	-	100 mpg	••
Seat Height	30.3 in 770 mm	•	30.7 in/780mm	-	29.0 in/736mm	-	28.3 in/719mm	•	31 in/787 mm	-	n.a.	
Fuel tank	1.9 gal 7 litres	•	1.2 gal./4.6 liters		1.3 gal./5 liters	-	1.2 gal./4.6 liters	-	1.32 gal./5 liters		n.a.	
Storage under seat	Holds a flip up helmet	•	1 helmet, 23 litres	•	n.a.	-	1 helmet, 22 litres	٢	n.a.		n.a.	
Brakes Front	Disc 220mm	•	Disc 185mm	:	Drum 95mm	-	Drum with CBS	-	Disc 180mm	:	Drum (size N/D)	-
Brakes Rear	Drum 140mm	•	Drum (size N/D)	:	Drum 95mm	-	Drum with CBS	:	Drum 110mm	:	Drum (size N/D)	
Front wheel	120/70 –14	•	120/90-10	-	130/90-10	-	80/100-10	-	130/70-12	-	90/90-10	••
Rear wheel	120/70 –14	•	120/90-10		130/90-10		80/100-10	-	130/70-12	-	90/90-10	-
MSRP	\$1,999	•	\$2,590		\$2,649	-	\$1,999	•	\$1,499	•	\$1,999	٢

SR-Motard 50 - Technical Specifications

	SR-Motard 50						
Engine	Air-cooled 4-stroke single-cylinder 4-valves engine, 49 cm ³						
Bore and Stroke	39 mm/41,35mm						
Compression ratio	12 ± 0.5:1						
Max. power	3.4 kW at 9,500 rpm						
Max. Torque	3.8 Nm at 8,000 rpm						
Fuel system	Keihin NCV φ20 carburetor						
Starter	Electric and kick start						
Ignition	Electronic inductive ignition with variable advance						
Lubrication	Wet sump forced lubrication system with mechanical pump						
Transmission	Automatic CVT, "twist and go"						
Clutch	Automatic centrifugal dry clutch						
Primary / Secondary drive	V belt / Gears						
Chassis	High-strength steel single cradle						
Front suspension	Telescopic hydraulic fork, stroke: 76mm						
Rear suspension	Engine acts as a swingarm, one hydraulic shock absorber with preload adjustment; stroke: 86mm						
Front brake	220 mm disc brake with two-piston floating caliper						
Rear brake	140 mm drum brake						
Rims	Light alloy						
Front tire	Tubeless, 120/70 14"						
Rear tire	Tubeless, 120/70 14"						
Dimensions							
Length	76.3 in 1,940 mm						
Width	28.3 in 720 mm						
Wheelbase	53.1 in 1,350 mm						
Saddle height	30.3 in 770 mm						
Fuel tank capacity	1.8 us gal. (0.39 us gal reserve) - 7 litres (1.5 liter reserve)						
Helmet compartment	Holds a flip up helmet						

aprilia

SR-Motard 50 – Colors & Prices



Price

MSRP \$ 1,999 (USA)

Available in Dealerships

MY14 Available from May 2013

Available Colors



SR-Motard 50 – Accessories



- Top Case Kit
- Capacity: 32 liters
- Color: Satin black



Pictures in this document refer to test model, slight changes might apply.